

STANDARD ACCESSORIES

CLEAR-LOCK COUPLER

- ▶ Clear midsection gives added visibility during installation, removing all guesswork from the process
- ▶ Visual confirmation of the pipe within the coupler ensures that it has been properly seated at the center stop
- ▶ Ideal for pull boxes, vaults or other limited access areas
- ▶ Non-metallic construction provides excellent corrosion resistance in buried or encased applications and also has desirable dielectric properties
- ▶ Simple, one person 'push-on' assembly lowers installation costs
- ▶ Self-locking ring design assembles in seconds and is re-enterable
- ▶ High strength molded plastic body is ideal for buried duct applications
- ▶ Pre-lubricated O-ring is water-tight and air-tight
- ▶ Suitable for both cable pulling & jetting applications



ORDER REFERENCE

DESCRIPTION	NOM OD	DUCT OD WORKING RANGE	LENGTH (IN)	PULL OUT STRENGTH (LBS)	MAX PRESSURE (PSI)	CARTON QTY	PART #
1/2" Clear-Lock	0.840"	0.830" - 0.850"	2.7"	400	250	180	20005878
3/4" Clear-Lock	1.050"	1.040" - 1.060"	3"	500	250	144	20005661
1" Clear-Lock	1.315"	1.305" - 1.325"	3.6"	600	250	50	20005662
1 1/4" Clear-Lock	1.660"	1.650" - 1.670"	5"	700	250	50	20005096
1 1/2" Clear-Lock	1.900"	1.890" - 1.910"	5.5"	800	250	25	20005663
2" Clear-Lock	2.375"	2.365" - 2.385"	7"	2000	250	15	20005097



An Orbia Connectivity Solutions business.

+1 800 847 7661
WWW.DURALINE.COM

TL9000

